

Step Up Your Sidewalk Game: Find the Perfect Solution for Every Job

SCOUT^{SR}

SR

MAG^{SR}



Implements & Attachments	Scout	Snowrator	MAG	Electrical	Scout	Snowrator	MAG
4'2" XT				Electric Start			
4' Straight-Blade				Battery CCA	350 A	350 A	690 A
5' Straight-Blade				Charging System	18 A	18 A	25 A
STX48 Snow Thrower				Keyed Power			
BRX48 Broom				Front Lights	2 STD	2 STD	2 STD
BKT40 Snow Bucket				Rear Light	1 STD	1 STD	1 STD
Exact Path				Lumens per Light	1200	1200	1200
TGS85							
40 Gal Brine Kit							
20 Gal Brine Kit							
Carry Trays				Lumens Total	3600	3600	3600
Bucket Mount							
Enclosure							

The Right Power for Any Job

Engine	Scout	Snowrator	MAG	Speed	Scout	Snowrator	MAG
Displacement	429 cc	429 cc	747 cc	Forward	6 MPH	5 MPH	8 MPH
Engine Manufacturer	Kohler*	Kohler*	Kohler*	Reverse	4 MPH	3 MPH	4 MPH
Engine Type (EFI or Carb)	Carb	Carb	EFI		Scout	Snowrator	MAG
Electronic Throttle body				4x4			
Cooling System	AIR	AIR	AIR	4x2			
Fuel	GAS	GAS	GAS	Type	Skid-Steer	Skid-Steer	Skid-Steer
Fuel Capacity	1.85 GAL	1.85 GAL	8.0 GAL				
*Kohler Energy has rebranded as Rehlko. Engine manufacturer may be labeled as either Kohler or Rehlko during this transition.							

Where Power Meets Versatility

Vehicle	Scout	Snowrator	MAG	Vehicle	Scout	Snowrator	MAG
Turning Radius	Zero Turn	Zero Turn	Zero Turn	Length (in)	73.5"	77.31"	60"
Approach Angle	33.5 degrees	21.5 degrees	47 degrees	Width (in)	34	38.5"	39.25"
Departure Angle	22 degrees	21.8 degrees	28.72 degrees	Height	48"	54.16"	52"
Break Over Angle	54 degrees	71.7 degrees	57.6 degrees	Weight (lb)	800 lbs	827 lbs	1046 lbs
Light Height/Angle (in)	11.81"	11.81"	14.28"	Wheelbase (in)	25"	24"	26.5"
Down Pressure Angle	5 degrees	15.3 degrees	17.5 degrees	Tires	18x8.5-10	18x8.5-10	18x8.5-10
Ground Clearance (in)	5.25"	5.17"	6"	Chassis	Mild steel	Stainless steel	Stainless steel
Lift Height Capability	32 degrees	25 degrees	25 degrees				

Mastering Efficiency

Hydraulics	Scout	Snowrator	MAG	Operator Features	Scout	Snowrator	MAG
High Flow Hydraulics				Cup Holder			
Low Flow Hydraulics Circuits	2	2	2	Foldable Operator Platform			
High Flow Hydraulics (QDC)				On-Board Diagnostics			
Low Flow Hydraulics (QDC)				Operator Warming			
2 Year Warranty				12-Volt Charging Port			